



HIGH QUALITY ☒

LOW ODOR ☒

DURABLE ☒

All Purpose Jointing Compound

TECHNICAL DATA SHEET

DOVA PRO

High-quality Ready-made putty modified with special polymers gives the product suitable flexibility and a strong bond. One component for all three coat applications.

Product Description

Dova Pro is an air-drying product. Give smooth, hard, and able to paint surfaces. Ideal for use as a painting putty on cement mortar, Gypsum mortar, and Gypsum board. Suitable for all plasterboard joints.

Standers

Dova Pro is formulated to comply with

- EN 13963 type 3A
- EN 13279 standers
- Egyptian standards 188-1/2013 C7

Product characteristics

- Exact mixing ratio and homogeneity of the mixture
- Easy application by hand or mechanical tools
- Can be sanded by hand
- High bonding strength with smooth surfaces
- White, smooth, and able to be painted

Application

- Surface must be clean and free from dust and oil.
- Please adjust your suitable viscosity by adding water
- Use as joint filler for gypsum board and as skim coat for the full surface of gypsum board
- Applied with hand application technique using a putty knife
- Leave the 1st layer to dry at least 24 hours before applying the 2nd layer

Packaging

Dova Pro is available in 20, 5 Kg pail

Storage

Shelf life is 12 months from production date in a dry and covered storage area

Safety data

Dova Pro is a nontoxic material. PH value is near to 7 so it doesn't affect the human skin or cause irritation for the hand.

Please if the end product reaches to eye or skin wash it well with clean water and soap.

